



- Beschreibung:**
- > Ladegerät für 2V, 6V und 12V Bleiakkus (Blei-Gel, Blei-Vlies, Blei Säure)
 - > Mit 3,5m langem Ladekabel
 - > Elektronischer Schutz gegen Kurzschluss, Verpolung und Überladung
 - > Geeignet für Bereitschafts- und Parallelbetrieb
 - > Ladung nach IU-Kennlinie
 - > Automatische Nachladung, wenn die Batterie am Gerät angeschlossen bleibt
 - > Ideal zur Überwinterung von Bleiakkus – Tiefentladung ausgeschlossen
 - > Batteriekapazität: 1,2Ah - 40Ah
 - > Gewicht: nur 135g durch moderne Schaltnetztechnologie
 - > Betriebsspannung: 100V - 240V AC / 50Hz - 60Hz
 - > Ladestrom: 400mA

- Description:**
- > Lead acid charger for 2V, 6V and 12V lead acid, SLA batteries
 - > With 3.5m charging cable
 - > Protection against short-circuit, wrong polarity and overcharge
 - > Suitable for standby and parallel mode
 - > Charging according to IU characteristic
 - > Automatic recharge, if the battery is left connected to the charger
 - > Ideal maintenance of lead acid batteries during winter time – no deep discharge
 - > Battery capacity: 1.2Ah - 40Ah
 - > Weight: only 135g due to modern switching power supply technology
 - > Operating voltage: 100V - 240V AC / 50Hz - 60Hz
 - > Charging current: 400mA

INFOS | INFORMATION:

Produktname | Product name:
PbBC-ALCS2-12 0.4-EU-cb

Art.-Nr. | Part No.:
1001-0015

EAN-Code:
4013674021727

Verpackungseinheit | Packing Unit:
10 (285x155x160mm)

Lieferbar | Available:
KW 01-2014 | week 01-2014

Zolltarifnummer | Customs tariff number:
85044055

UVP | MSRP:
19,99 €

Materialgruppe | Material Group:
01



Notizen / Notes:



PbBC-ALCS2-12/0.4-EU-cb