

I'VE GOT THE POWER2GO

Your transportable Energy
Storage System



E-Mobility



Drive
System



Energy Storage
Systems



Power- and
Gardentools



Industrial



Medical

TECHNICAL DETAILS



| Technical details | POWER2GO LIFE | POWER2GO WORK |
|----------------------------|---|-------------------------------------|
| Cell type | Lithium-Ionen | Lithium-Ionen |
| Energy content | 2.500 Wh | 2.500 Wh |
| Nominal power | 2.500 W | 2.500 W |
| Max. power | 3.600 W | 3.600 W |
| Charging voltage | 92-264 Vac | 92-264 Vac |
| Charging power | 1.000 W | 1.000 W |
| AC output @230Vac | 1x 230 V (safety plug) | 2x 230 V (safety plug) |
| 1x AC-Input | C14 connector (cold appliance plug) | C14 connector (cold appliance plug) |
| Net weight | ~23 kg | ~23 kg |
| Dimension | ~452x373x192 mm (not fixed) | ~471x507x227 mm (not fixed) |
| Operating temperature | ~10 to 65°C | ~10 to 65°C |
| Extras | Display, light, LED indicator for current use | LED display for current use |
| Material of the housing | Aluminium | Aluminium |
| IP class | IP65 | IP65 |
| Certification | UN 38.3, CE | UN 38.3, CE |
| Charging with solar panels | <500 W | <500 W |

NO SOCKET? NO PROBLEM!









We like to pull out the power bank for our smartphone in our private lives. But what if we need more power?

Time for POWER2GO!

Let's think bigger! **POWER2GO** was designed for demanding users. Designed to be dustproof and waterproof, **POWER2GO** is a robust companion for all occasions.

That goes in the back? No way! Carrying with one hand? You can do it with your left hand! **POWER2GO** impresses with its extremely high power density and weighs just 23 kg!

POWER2GO replaces your stationary power connection. Devices with up to 3,600 W peak power can be operated with the **POWER2GO** without any problems. Constant, long-term power output of 2,500 W. All this is offered by **POWER2GO**, your reliable power supply for on the go.

| | | |
|---|---------------|------------|
|  | 10W | 15.000 min |
|  | 65W | 2.280 min |
|  | 420W | 360 min |
|  | 800W | 200 min |
|  | 1.000W | 150 min |
|  | 1.200W | 124 min |
|  | 1.200W | 125 min |
|  | 2.200W | 70 min |

SOLAR PANEL IN THE BUNDLE

Secure your offer now at
www.bmz-group.com



Do you have any questions?

Contact us, we will be happy to advise you.

Headquarter

BMZ Germany GmbH

Zeche Gustav 1
63791 Karlstein am Main
Deutschland

T: +49 6188-9956-0
E: mail@bmz-group.com

BMZ USA Inc.

1429 Miller Store Road
Virginia Beach
VA 23455
USA

T: +1-757 821-8494
E: contact-usa@bmz-group.com

BMZ Company Ltd.

Julong Technology Building B
Cuibao Road, Longgang District,
Shenzhen, Guangdong Province
P.R.China 518116

T: +86 755 8977 5800
E: contact.cn@bmz-group.com

BMZ Poland Sp. z o.o.

Alberta Einsteina 9
44-109 Gliwice
Polen

T: +48 327842 450
E: BMZPolandSales@bmz-group.com

BMZ Innovation Group Ltd.

Future Business Centre
Kings Hedges Road
Cambridge, CB4 2HY
United Kingdom

T: +44 7391 351787
E: lukas.gazda@bmz-group.com

BMZ Japan KK

Shitaya 1-6-5, Taito-ku,
Tokyo, 110-0004
Japan

T: +81 35811 1973
E: tokio.kobayashi@bmz-group.com

BMZ France S.A.R.L.

153 Boulevard Haussmann
75008 Paris
Frankreich

T: +33 06 84 52 76 29
E: nicolas.noel@bmz-group.com

www.bmz-group.com



© BMZ 2023

All rights reserved. Preliminary data sheet. Although great care has been taken in the preparation of this data sheet, BMZ assumes no responsibility for any errors or omissions. All information contained herein is subject to change without notice.