



SPECIFICATIONS

**FOR EBV E-BIKE BATTERY, COMPATIBLE TO
BOSCH* ACTIVE (PLUS) / PERFORMANCE (CX) DRIVE SYSTEM WITH 36 V**

Power information

15 Ah / 540 Wh Downtube Battery



312 x 94 x 80 mm

CONTENT

Technical information.....3

Charging.....3

Discharging3

Intelligent eBV Battery Management System (BMS), Gen. 33



Akku Vision GmbH
Industriestraße-West 6
D-63808 Haibach

Phone: +49 (0) 6021 3289288
Email: info@akkuvision.de
Web: www.akkuvision.de

E-Bike Vision is a trademark of the Akku Vision GmbH

Technical information

Li-Ionen battery	15 Ah / 540 Wh
Nominal voltage	36 V
Nominal capacity	15 Ah
Energy	540 Wh
Cell Configuration	10 Series 3 Parallel
Mounting	Downtube
Dimensions	312 x 94 x 80 mm
Weight	2800 g

Charging

- Constant Current / Constant Voltage
- Max. 8 A charge current

Discharging

- 15 A continuous discharge current
- 24 A for 3 s
- 30 A for 200 ms

Intelligent eBV Battery Management System (BMS), Gen. 3

Safety Features

- Control of cell and BMS temperature
- Single cell voltage monitoring
- Passive cell balancing
- Battery pack voltage monitoring
 - over voltage protection (cells & pack)
 - deep discharge protection (cells & pack)
- Battery pack current monitoring
 - for charging
 - for discharging
 - short-circuit protection

Communication port

- CAN Bus (Bosch Active / Performance compatible)
- Compatible with Bosch Diagnostic Tool
- Integrated Bluetooth Chip for firmware updates

SoC (State of Charge) Display

- 5 LEDs and communication to HMI