

e-bike-vision.de

Get more range!



Replacement battery Lite, compatible to Bosch Active (Plus) / Performance (CX) 36V drive system*

^{*} All brands and product names are registered trademarks of their respective manufacturers

_		• 1		
Tec	nn	ハコ	1 11:	コナコ・
ICL		ıca	ıu	ata.

- Nominal Voltage:
 - o 36.0 V (50E)
- Nominal Capacity:
 - o 10.0 Ah (50E)
- Nominal Energy:
- o 360.0 Wh (50E)
- Cell Configuration:
 - o 10 series
 - o 2 parallel
- Chemical System:
 - o LiNiCoAlO2
- Cell Type:
- Samsung INR21700-50E (360.00 Wh)
- Dimensions:
 - L x W x H: 268.2 x 80.0 x 76.6 mm (Downtube)
 - L x W x H: 341.3 x 118.0 x 76.2 mm (Carrier)
- Weight:
 - 1.800 g (Downtube)
 - o 2.000 g (Carrier)

- Charging:
 - ConstantCurrent / ConstantVoltage
 - Max. 8 A charge current
- Discharging:
 - 15 A continuous discharge current
 - 24 A for 3 s
 - **30** A for 200 ms
- Intelligent eBV BatteryManagementSystem (BMS), Gen.3
 - Safety Features:
 - Control of cell and BMS temperature
 - Single cell voltage monitoring
 - Passive cell balancing
 - Battery pack voltage monitoring
 - over voltage protection (cells & pack)
 - deep discharge protection (cells & pack)
 - Battery pack current monitoring
 - for charging
 - for discharging
 - short-circuit protection
 - Occupant of the contract of
 - CAN Bus (Bosch Active / Performance compatible)
 - compatible with Bosch DiagnosticTool
 - integrated Bluetooth Chip for firmware updates
 - SoC (State of Charge) display: 5 LEDs and communication to HMI