



11KW&22KW EV CHARGER

Specifications

MODEL	AX-A11KP1-UK	AX-A22KP1-UK
TYPE	CHARGING PLUG	CHARGING PLUG
INPUT		
Wiring Scheme	3P+N+PE	
Voltage	400Vac, ±20%	
Maximum Current	16A	32A
Frequency	50/60Hz	
OUTPUT		
Voltage	400Vac, ±20%	
Maximum Current	16A	32A
Rated Power	11kW	22kW
USER INTERFACE & CONTROL		
Connector Type	Type 2 cable	
RFID Reader	Mifare ISO/IEC 14443 A	
Start Mode	Plug&Play/RFID card/App	
Communication		
WiFi, Bluetooth	Yes	
OCPP	OCPP 1.6 JSON, OCPP 2.0 optional	
Environment		
Installation	Wall-mount / Post-mount	
Operating Temperature	-30°C ~ 50°C	
Operating Humidity	5% ~ 95% No condensation	
Operating Altitude	≤2000m	
DIMENSION AND WEIGHT		
Product Dimension	320*190*130 mm	
Product Weight	5.43kg	
Safety		
IP protection rating	IP65	
IK protection rating	IK08	
Residual Current Detection	AC 30mA/DC 6mA	
Electrical Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over temperature protection	
EMC	Class B	
Certification	UKCA	
Certification Standard	EN/IEC 61851-1: 2019, EN/IEC 61851-21-2: 2021	EN/IEC61000-6-1/2/3/4:2019

No liability for printing errors. Subject to errors and prior sale. Illustrations similar.



AKKU SYS Akkumulator- und Batterytechnik Nord GmbH

Verbindungsweg 23 · 25469 Halstenbek · GERMANY

Phone +49 4101 37676-0 · Fax +49 4101 85475-66 · info@akkusys.de · www.akkusys.de · akkusys.shop

atx006en0623